



The Micro 3001 and 3002 are new satellite speakers. But don't let their small size fool you. These are serious speakers and they employ custom transducers and elaborate crossovers to provide a detailed sound that is loud and clear. The enclosure is ABS (moulded plastic) that gives the Micro a unique shape which blends into your living space. The products are sold separately or as a Micro HTS package with the rugged Roarr 1108. You may install the Micros using the keyhole slot or with universal brackets (included). So if you are looking for high quality music or cinema sound experience in your premium space, choose the new Micro from Sonodyne.



	MICRO 3001	MICRO 3002
DESCRIPTION	2 way speaker , ported	2 way speaker , ported
ENCLOSURE	ABS	ABS
TRANSDUCER COMPLEMENTS: HF	0.5" polycone tweeter	0.5" polycone tweeter
LF	3" woofer	2 x 3" woofer
REC. AMPLIFIER POWER	40 ~ 100W	40 ~ 120W
NOMINAL IMPEDANCE	8Ω	8Ω
SENSITIVITY (1W/1M)	87dB	90dB
FREQUENCY RESPONSE (-3dB)	100Hz ~ 20kHz	100Hz ~ 20kHz
FREQUENCY RANGE (-10dB)	80Hz ~ 22kHz	70Hz ~ 22kHz
CROSSOVER FREQUENCY	6.5kHz	3.5kHz
INPUTS	Binding post	Binding post
COLOURS	Black / White	Black / White
DIMENSIONS (HxWxD)	171mm x 100mm x 108mm	100mm x 261mm x 100mm
NET WEIGHT	0.75kg	1.3kg
MOUNTING OPTIONS	Wall mount bracket (included)	Wall mount bracket (included)
PACKED IN	Pairs	Single

	MICRO SUB 100
DESCRIPTION	Front firing powered subwoofer ,vented
ENCLOSURE	MDF
TRANSDUCER COMPLEMENTS	1 x 8" high excursion subwoofer
AMPLIFIER CLASS & POWER	Class AB, 100W
AMPLIFIER THD	0.1% at rated power
MAX SPL	109dB
FREQUENCY RESPONSE	35Hz (-3dB)
FREQUENCY EXTENSION (-10dB)	30Hz
LOW PASS FILTER	50Hz ~ 150Hz
PHASE	Switchable: 0° and 180°
INPUTS	Left and Right unbalanced RCA type
INPUT SENSITIVITY	80mV at level control max
CONTROLS	Level control, frequency control
FINISH	Black
DIMENSIONS (HxWxD)	330mm x 330mm x 429mm
NET WEIGHT	11.7kg