

ON-WALL SPEAKERS

SONODYNE®

SOW SERIES



- 3 models
- 2 way design
- Direct & LMT connectivity
- Polypropylene moulded enclosure
- Wall mount included
- Outdoor use ready (IP65)

	SOW 6160	SOW 6150	SOW 6140
DESCRIPTION	IP65 weather resistant speaker	IP65 weather resistant speaker	IP65 weather resistant speaker
TRANSDUCERS	1 x 6" woofer, 1 x 1" dome tweeter	1 x 5" woofer, 1 x 1" dome tweeter	1 x 4" woofer, 1 x 1" dome tweeter
FREQUENCY RESPONSE (±6dB)	60Hz ~ 20kHz	80Hz ~ 20kHz	90Hz ~ 20kHz
SENSITIVITY 1W/ 1M half space	90dB	88dB	86dB
MAX SPL DIRECT MODE	109dB	105dB	102dB
NOMINAL IMPEDANCE	8Ω	8Ω	8Ω
POWER HANDLING (direct mode)	80W	60W	40W
POWER TAPS, 70V 100V	3.75W, 7.5W, 15W, 30W 7.5W, 15W, 30W, 60W	1.77W, 3.75W, 7.5W, 15W 3.75W, 7.5W, 15W, 30W	1.25W, 2.5W, 5W, 10W 2.5W, 5W, 10W, 20W
COLOUR	White/ Black	White/ Black	White/ Black
DIMENSION (HxWxD)	200mm x 303mm x 181mm	176mm x 252mm x 148mm	136mm x 196mm x 131mm
MOUNTING	Pan & tilt wall mount bracket (included)	Pan & tilt wall mount bracket (included)	Pan & tilt wall mount bracket (included)