

# PENDANT SPEAKERS

SONODYNE®



## SPS SERIES

- 3 models
- Smooth, balanced response
- Wide dispersion
- IP rated for outdoor use
- Ceiling, wall and ground mounts
- Black and white colours



	SPS 1040	SPS 1050	SPS 1060
DESCRIPTION	Pendant speaker	Pendant speaker	Pendant speaker
SYSTEM	Passive 2 way bass reflex	Passive 2 way bass reflex	Passive 2 way bass reflex
TRANSDUCERS	1 x 4" woofer, 1 x 3/4" dome tweeter	1 x 5" woofer, 1 x 1" dome tweeter	1 x 6.5" woofer, 1 x 1" dome tweeter
NOMINAL IMPEDANCE	8Ω	8Ω	8Ω
FREQ. RESPONSE (±6dB)	80Hz ~ 20kHz	65Hz ~ 20kHz	50Hz ~ 20kHz
POWER HANDLING	40W (direct mode)	50W (direct mode)	60W (direct mode)
POWER TAPS, 100V	2.5W, 5W, 10W, 20W	3.75W, 7.5W, 15W, 30W	5W, 10W, 20W, 40W
70V	1.25W, 2.5W, 5W, 10W	1.77W, 3.75W, 7.5W, 15W	2.5W, 5W, 10W, 20W
SENSITIVITY 1W/1M	83dB	85dB	88dB
MAX SPL DIRECT MODE	100dB	103dB	106dB
GRILLE	Aluminium mesh powder coated	Aluminium mesh powder coated	Aluminium mesh powder coated
ENCLOSURE MATERIAL	Polypropylene	Polypropylene	Polypropylene
INPUT	Pluggable terminal block	Pluggable terminal block	Pluggable terminal block
WEATHERISED RATING	IP65	IP65	IP65
COLOUR	Black and white	Black and white	Black and white
PACKING	Single	Single	Single
DIMENSIONS (DIA x HEIGHT)	155mm x 215mm	190mm x 250mm	230mm x 300mm
NET WEIGHT	1.9kg	2.55kg	3.45kg
MOUNTING	Wire rope for hanging (included), wall-mount bracket, floor-mount bracket optional	Wire rope for hanging (included), wall-mount bracket, floor-mount bracket (optional)	Wire rope for hanging (included), wall-mount bracket, floor-mount bracket (optional)