

COLUMN SPEAKERS

SONODYNE®



CA SERIES

- 2 models
- 2 way design
- Aluminium cabinet
- Direct and LMT connectivity
- Wall mount provision
- Black/ white colour
- IP 66 rated version available



CS SERIES

- 2 models
- 2 way column speakers
- Aluminium extruded enclosure
- Sturdy swivel bracket
- Both direct and LMT connectivity

A-LIGN 400S

- Monopole line array including 16 drivers
- Wide horizontal coverage
- 2 way design
- Aluminium cabinet
- Wall mount provision
- Black/ white colour



DESCRIPTION	2 way monopole line array
ENCLOSURE	5mm extruded aluminium with PU paint
GRILL	Perforated nylon
TRANSDUCER COMPLEMENTS	8 x 3" pp cone woofer 8 x dome tweeter with wave guide
INPUT	Twist lock
PARALLEL LINK	Euroblock
SENSITIVITY (1W/1M) half space	94dB
MAXIMUM SPL	121dB
NOMINAL IMPEDANCE	4Ω
CROSSOVER FREQUENCY	1.8kHz
FREQUENCY RESPONSE (-3dB)	180Hz ~ 20kHz
FREQUENCY RANGE (-10dB)	140Hz ~ 25kHz
COVERAGE PATTERN	110° H x 20° V
CONTINUOUS POWER HANDLING	200W
RECOMMENDED AMP POWER	300W
DIMENSIONS (HxWxD)mm	1194 x 125 x 110
NET WEIGHT	9.8kg
MOUNTING OPTIONS	A400 PM, A400 WB

Recommended amplification by Australian Monitor

	CA 410	CA 820	CS 210	CS 220
DESCRIPTION	2 way column speaker	2 way column speaker	2 way column speaker	2 way column speaker
ENCLOSURE	3mm extruded aluminium	3mm extruded aluminium	3mm extruded aluminium	3mm extruded aluminium
GRILL	Perforated nylon	Perforated nylon	Perforated metal	Perforated metal
TRANSDUCER COMPLEMENTS	4 x 3" pp woofer 1 x 1" dome tweeter	8 x 3" pp woofer 1 x 1" dome tweeter	4 x 2" woofer 1 x 1" dome tweeter	8 x 2" woofer 1 x 1" dome tweeter
INPUT	Euroblock	Euroblock	Euroblock	Euroblock
SENSITIVITY (1W/ 1M) half space	93dB	95dB	98dB	91dB
NOMINAL IMPEDANCE(direct mode)	8Ω	4Ω	8Ω	4Ω
CROSSOVER FREQUENCY	2.6kHz	1.8kHz	6kHz	6kHz
FREQ. RESPONSE (-3dB) (Direct Mode)	150Hz ~ 15kHz	140Hz ~ 18kHz	180Hz ~ 18kHz	180Hz ~ 18kHz
FREQ. RANGE (-10dB) (Direct Mode)	120Hz ~ 20kHz	110Hz ~ 20kHz	160Hz ~ 20kHz	160Hz ~ 20kHz
PROGRAM POWER (Direct Mode)	80W	150W	60W	120W
POWER TAPS @ 70V	1.25, 2.5, 5, 10W	3.75, 7.5, 15, 30W	1.25, 2.5, 5, 10W	1.9, 3.75, 7.5, 15W
POWER TAPS @ 100V	2.5, 5, 10, 20W	7.5, 15, 30, 60W	2.5, 5, 10, 20W	3.8, 7.5, 15, 30W
DIMENSIONS (HxWxD) mm	579 x 125 x 110	878 x 125 x 110	430 x 85 x 85	660 x 85 x 85
NET WEIGHT	4kg	6kg	2.5kg	4kg
MOUNTING OPTIONS	Swivel bracket (included)	Wall mount (optional)	Swivel bracket (included)	Swivel bracket (included)
COLOUR	White/ black	White/ black	White/ black	White/ black
WALL MOUNT	A400 WB	A400 WB	Included	Included