

## SH SERIES



	SH 15	SH 30
PROGRAM POWER RMS	15W	30W
SPEAKER TAPS	15W, 7.5W, 3.8W, 1.9W, 8 Ohm	30W, 15W, 7.5W, 3.8W, 8 Ohm
FREQ. RESPONSE (-10dB) ±5dB, HALF SPACE	370Hz ~ 5.5kHz	350Hz ~ 5kHz
FREQ. RESPONSE (-40dB) ±5dB, HALF SPACE	200Hz ~ 14.5kHz	200Hz ~ 11kHz
SENSITIVITY (1W/1M PINK NOISE)	97dB	98dB
MAXIMUM SPL (1W/1M CONTINUOUS POWER / PEAK POWER)	108dB/111dB	112dB/115dB
COVERAGE ANGLE	120° conical	108° conical
DRIVER	34mm compression driver	40mm compression driver
IP RATING	IP66	IP66
CONSTRUCTION	Flare - Aluminium. Housing - ABS UL-94HB; UV Stabilized	Flare - Aluminium. Housing - ABS UL-94HB; UV Stabilized
COLOUR	(White) RAL 9010	(White) RAL 9010
SPEAKER CABLE	36SWG, 25 strands, inner insulator 2mm, outer insulator 6mm, length 1m	36SWG, 25 strands, inner insulator 2mm, outer insulator 6mm, length 1m
BRACKET	U shaped Zinc-rich powder-coated steel	U shaped Zinc-rich powder-coated steel
DEPTH	210mm	258mm
DIAMETER	210mm	258mm
WEIGHT	264mm	310mm

*Due to continuous improvements, all specifications are subject to change*